

ER-1600 has much 12 atures with ea 7 attractive

is I 40

22



Password security system (NEW)

nobody can set or revise it without Password A4 - digit password protects program data so that

Daylight saving time (Summer time)

daylight saving time ER-1600 can switch automatically to and from

3 years memory back up

and program data for three years Built-in lithium battery protects the clock, calendar

Wall mounting

S 11 8

supplied complete with locking bracket. Easy installation for wall mounting Perfect fitl

Multi-viewing positions



standard vertical position or laying under a counter, etc. flat on a table, inside a drawer, The display can be viewed in the

Fully automatic system can protect time card from over stamp Fully automatic without any key operations

Up to 4 columns

Two "IN" and two "OUT" columns are available

Additionally, an extra column for "Daily Total Time"

style of "Daily Total Time.") (Either "Regular work time" or "Overtime" is available as the Calculates and prints "Daily Total Time" in the 5th column

Can print not only in regular minutes but also in 1/100th of hours Printing in regular minutes or 1/100th of hours

Symbols-Late in, Early out and Overtime

printing each time. Overtime " # " ER-1600 can recognize and print Late-in "▶", Early-out "∢", , and Overnight " \star ", automatically when

3 kinds of pay period format

Selectable 3 pay periods: Monthly, Bi-weekly and Weekly

Next Day Overtime Key

Line change can be extended past midnight or Line Shift Time

Angled insertion of time card

every time. Easy and comfortable to stamp



Specification

opecifications	
Production description	Production description Max Electronic Time Recorder ER-1600
Power supply	Europe AC230V 50/60Hz 0.2A
fiddae issue	Other countries AC220/230V 50/60Hz 0.2A
Outside dimensions	202(H) × 140(W) × 104(D)mm
Weight	1.8kg
Clock system	Crystal quartz oscillation Monthly tolerance ±15 seconds (Normal temperature : 25℃/ 77°F)
Display	Data, Hour, Minute, AM/PM, Day of week, V, DED, X, X.
Printed information	Data, Hour/Minute (Up to 4 columns), Daily Total Time Symbol of \P , \triangleright , Ψ , \star .
Guarantee in case of power failure	Memory backup supported by an internal battery and a clock function guaranteed over a period of 3 years as accumulated power failure after assembling at factory.
Capacity	50 or 150 employees
Time card/ink ribbon	MAX ER-M time card ER-IR 103 ink ribbon cassette
Operation temperature	0°C~40°C/32°F~104°F
Storage temperature	-20°C ~ 60°C/-4°F ~ 140°F

The specifications and design of the products in this catalogue will be subject to change without advance notice due to our continuous efforts to improve the quality of our products.



Distributor: